

# 5/6" Seamless Rollformer



## Polyurethane Drive Train

- Eliminates the need to load coil prior to transportation (less material waste)
- Rollform 24 gauge steel
- Eliminates slippage from cold weather and condensation

# .002 Hard Chrome Plated Steel Forming Rollers

- Rollforms all recommended materials with minimal or no adjustment
- Free-floating forming rollers produce less pressure and allow for more product uniformity

#### **Electrical and Control System**

- Push button entry and exit end controls with safety wiring and "jog" feature
- 3/4 HP, 110 volt, single phase motor, 13.6 ampere

#### Structural Steel Frame

Welded tubular frame

# Modular Turnstile Upright System & Transfer Bars

Transfer bars (ease of coil loading)

2 YEAR WARRANTY ON PARTS & LABOR





# 5/6" Seamless Rollformer

#### Power

3/4 HP, 110 volt, single phase, 13.6 ampere, totally enclosed fan cooled (T.E.F.C.) motor

#### Dimensions

Length – 122" (309.88 cm) Height – 48" (122.0 cm) Width – 24" (61.0 cm)

# Weight

Approximately 1,400 lbs. (635 kg)

#### Drive

Powered polyurethane drive rollers via chains and sprockets

#### Shear

5" - Front pull guillotine 6" - Front pull guillotine

#### Speed

Approximately 35 feet per minute

#### Controls

Push button entry and exit end controls with "jog" feature

#### Recommended Materials

Maximum width 5" – 11 3/4" to 12" Maximum width 6" – 15"

MaterialMaximum GaugePainted steel24Aluminized steel24Ternecoat steel24Aluminum.032

Copper 16 oz. - 20 oz. 3/4 hard

### Options

- Machine mount cradles
- Additional runout support stands
- CE Certified wiring
- Additional turnstiles
- Additional spools
- Alcoa style hook
- 12 volt, DC power
- Box gutter
- Roof flange 1"
- Trailer riser pad



Quick release turnstile and transfer bars



795 South Larkin Avenue Rockdale, Illinois 60436

Phone (815) 725-9205 • Fax (815) 725-4429

Toll-free (888) 729-4290

E-mail sales@kwmgutterman.com www.kwmgutterman.com