RON MAN 5 1/2" Fascia Gutter



New upright, tension brake, aluminum spool and coil scale

Polyurethane Drive Train

- Eliminates the need to load coil prior to transportation (less material waste)
- Eliminates slippage from cold weather and condensation
- Rollforms all standard metals with minimal or no adjustment

Electrical and Control System

- Push button entry and exit end controls with safety wiring and "jog" feature
- 3/4 HP, 110 volt, single phase motor, 13.6 ampere

Structural Steel Frame

Welded tubular frame

Modular Turnstile Upright System



2 YEAR WARRANTY

ON PARTS & LABOR

RON MAL

www.kwmgutterman.com Toll-free (888) 729-4290



Power

3/4 HP, 110 volt, single phase, 13.6 ampere, totally enclosed fan cooled (T.E.F.C.) motor

Dimensions

Length – 132 1/2" (336.55 cm) Height – 48" (122.0 cm) Width – 24" (61.0 cm)

Weight Approximately 1,300 lbs. (589.7 kg)

Drive

Powered polyurethane drive rollers via chains and sprockets

Shear Front pull guillotine

Speed Approximately 35 feet per minute

Controls

Push button entry and exit end controls with "jog" feature

Recommended Materials

14" and 15" wide

MaterialMaximum GaugeAluminum.032Copper16 oz.-20 oz. 3/4 hard

Options

- Machine mount cradles
- Fixed upright system
- Additional runout support stands
- CE Certified wiring
- Additional turnstiles
- Additional spools
- Flange assembly for roofwing



Quick release turnstile and transfer bars



795 South Larkin Avenue Rockdale, Illinois 60436 Phone (815) 725-9205 • Fax (815) 725-4429 Toll-free (888) 729-4290 E-mail sales@kwmgutterman.com www.kwmgutterman.com