

# 5" Seamless Rollformer



- Eliminates the need to load coil prior to transportation (less material waste)
- Rollform 24 gauge steel
- Eliminates slippage from cold weather and condensation

# .002 Hard Chrome Plated Steel Forming Rollers

- Rollforms all recommended materials with minimal or no adjustment
- Free-floating forming rollers produce less pressure and allow for more product uniformity

# **Electrical and Control System**

- Push button entry and exit end controls with safety wiring and "jog" feature
- 3/4 HP, 110 volt, single phase motor, 13.6 ampere

# Structural Steel Frame

Welded tubular frame

# Modular Turnstile Upright System & Transfer Bars

Transfer bars (ease of coil loading)

2 YEAR WARRANTY ON PARTS & LABOR





# 5" Seamless Rollformer

#### Power

3/4 HP, 110 volt, single phase, 13.6 ampere, totally enclosed fan cooled (T.E.F.C.) motor

#### Dimensions

Length – 98 1/2" (250.2 cm) Height – 48" (122.0 cm) Width – 24" (61.0 cm)

# Weight

Approximately 1,100 lbs. (499.0 kg)

#### Drive

Powered polyurethane drive rollers via chains and sprockets

# Shear

Front pull guillotine

# Speed

Approximately 35 feet per minute

# Controls

Push button entry and exit end controls with "jog" feature

# Recommended Materials

Maximum width 11 3/4" to 12 3/8"

Material	Maximum Gauge
Painted steel	24
Galvanized steel	24
Aluminized steel	24
Ternecoat steel	24
Aluminum	.032

Copper 16 oz.-20 oz. 3/4 hard

# Options

- Machine mount cradles
- Additional runout support stands
- CE Certified wiring
- Additional turnstiles
- Additional spools
- Alcoa style hook
- 12 volt, DC power
- Box gutter
- Roof flange 1"
- Trailer riser pad



Quick release turnstile and transfer bars



795 South Larkin Avenue Rockdale, Illinois 60436

Phone (815) 725-9205 • Fax (815) 725-4429

Toll-free (888) 729-4290 E-mail sales@kwmgutterman.com

www.kwmgutterman.com